# **SNAP-TITE** ATX

## HIGH PRESSURE NITRILE RUBBER ATTACK/SUPPLY HOSE

Manufactured in a similar process as TPX, ATX utilizes a 3-ply design where

the cover and liner are extruded independently and double vulcanized to guarantee a consistent, compact hose wall. The polyester reinforcement

can then be woven tighter, making this hose more resistant to puncture

while also being easier to pack and store. ATX has a stronger jacket which increases the service test pressure of the LDH sizes to 300 psi (2068 kpa).














## **FEATURES AND BENEFITS**

- 3-ply rubber municipal fire hose with both the cover and liner made of heavy duty nitrile rubber, high tensile strength tightly woven polyester reinforcement for maximum durability and flexibility.
- Smooth liner keeps friction loss to a minimum.
- Nitrile rubber cover greatly increases abrasion resistance, provides long service life and the tightly woven reinforcement resists puncture.
- Remains flexible to temperatures as low as -40°F (-40°C) and is resistant to ozone, oxidation, and most chemicals and petrochemicals.
- Suitable for pumping sprinklers and standpipes, industrial fire fighting, and supplying aerial devices.
- Manufactured in accordance with NFPA 1961 standard, latest edition within our ISO-9001:2015 certified quality assurance system.



#### CONSTRUCTION

3-Ply Nitrile Rubber Cover/Liner Polyester Reinforcement

#### **TEMPERATURE RANGE**

-40°F to 200°F (-40°C to 93°C)

#### COUPLINGS

Aluminum NH/NST or IPT Threaded & Aluminum Storz

#### **COLORS**

Yellow Red Orange

\*please contact us for additional colors available.

### **HOSE SIZING AND SPECIFICATIONS**

SIZE	SERVICE PRESSURE	WORKING PRESSURE	BURST PRESSURE	<b>WEIGHT</b> (FOR 50' COUPLED)	FLAT WIDTH
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN
4"	300 (2068)	600 (4137)	900 (6205)	60 (27.2)	7.00"
5"	300 (2068)	600 (4137)	900 (6205)	76 (34.5)	8.75"
6"	300 (2068)	600 (4137)	900 (6205)	82* (37.19)	10.25"

\*weight uncoupled

#### **HOW TO ORDER**

ТҮРЕ	HOSEID	ву	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
ATX	40 = 4" 50 = 5" 60 = 6"	х	<b>50</b> = 50' <b>100</b> = 100'	Y = Yellow R = Red O = Orange K = Black	40 = 4" 50 = 5" 60 = 6"	N = NH I = IPT S = Storz	<b>Blank</b> = Aluminum

