


# GLADIATOR™ FG



**Snap-tite**  
HOSE

Nitrile Rubber  
Liner

Polyester  
Outer Jacket



## CONSTRUCTION

Polyester Outer jacket

Extruded Nitrile Thru-the-Weave Inner Liner

## TEMPERATURE RANGE

-40°F to 200°F (-40°C to 93°C)

## COUPLINGS

Aluminum NH/NST or IPT Threaded

## HOSE COLORS



ATTACK



LOW PSI



CAFS



USA MADE



## PREMIUM HOSE. EXCELLENT FLOW, EVEN AT LOW PRESSURE.

Gladiator is a premier hose which has a polyester outside jacket that encompasses a very durable nitrile rubber thru-the-weave inside liner. Built to last, the rugged hose is constructed with incredible strength and long-lasting performance in mind. The Gladiator performs well at high or low pressures, has a smooth and enhanced waterway for better flows and less kinking than other products on the market.

## FEATURES

- Premium quality, outside jacket with a nitrile rubber thru-the-weave inner liner construction.
- Optional Dura-Cote™ treatment.
- Remains flexible to temperatures as low as -40°F (-40°C) and is resistant to ozone and oxidation.
- Kink resistance exceeds that of lightweight jacketed hose.
- Suitable for use with CAFS and foam solutions.
- Manufactured in accordance with NFPA 1961 Standard, latest edition within our ISO-9001:2015 certified quality assurance system.

## HOSE SIZING AND SPECIFICATIONS

SIZE	SERVICE TEST	PROOF TEST	BURST	WEIGHT (FOR 50' COUPLED)	FLAT WIDTH	ID*	BOWL SIZE
IN	PSI (kPa)	PSI (kPa)	PSI (kPa)	LBS (KG)	IN	IN	IN
1 3/4"	500 (3447)	1000 (6895)	1500 (10342)	22 (10)	3.39"	1.88"	2 3/16"
2"	500 (3447)	1000 (6895)	1500 (10342)	23 (10.4)	3.50"	2.01"	2 5/16"
2 1/2"	500 (3447)	1000 (6895)	1500 (10342)	35 (15.9)	4.37"	2.54"	2 7/8"

\*ID values derived from product specification with allowable manufacturing tolerances. For specific ID tolerance range for products please contact [engsupport@snaptitehose.com](mailto:engsupport@snaptitehose.com)

As per NFPA 1961 - The service test pressure is to be 10% greater than the "normal highest operating pressure" at which the hose is expected to be used.

## HOW TO ORDER

TYPE	HOSE ID	BY	HOSE LENGTH	COLOR	COUPLING SIZE	THREAD TYPE	COUPLING MATERIAL
FG	17 = 1 3/4" 20 = 2" 25 = 2 1/2"	X	50 = 50' 100 = 100'	Y = Yellow R = Red B = Blue O = Orange G = Green T = Tan C = White (coated)	15 = 1 1/2" 20 = 2" 25 = 2 1/2"	N = NH I = IPT	Blank = (Aluminum)

Part No. Example: **FG17X50Y15N** = FG Gladiator Hose, 1 3/4" ID by 50' Length, Yellow, 1 1/2" NH/NST Aluminum Coupling



[www.snaptitehose.com](http://www.snaptitehose.com)  
814-438-7616  
UPDATED 10/15/22