



Key Features

- High-resolution of 640 × 480 with 95° FOV provides premium image quality and enhanced scene overview. Firefighters can cover more space at once when sweeping rooms and detect victims, doors, and hazards more efficiently.
- Seamless single-range interface ensures uninterrupted focus with a simplified live image display and minimal menu interaction.
- Integrated wireless connectivity enables streamlined configuration, live streaming, and efficient media handling for mission support and training.

Main Applications

- Engineered for frontline firefighting with rugged IP67-rated construction, 2-meter (6.6 ft) drop resistance, and outstanding high-heat performance.
- Supports training and post-incident review through intuitive media extraction and wireless streaming for real-time feedback and analysis.
- Optimized for reliable thermal visibility in low-light and smoke-obscured environments.

www.flir.com/Kxx-Series

Specifications

Model	Flir K95
Imaging and optical data	
IR resolution	640 × 480
Thermal sensitivity, NETD	<70 mK
Field of view	95° × 74°
Image frequency	30 Hz
Spectral range	7.5 to 14 μm
Pixel pitch	12 μm
Detector type	Focal plane array (FPA), uncooled microbolometer
Image representation	
Display	4" LCD, 640 × 480, backlit
Display frame rate	60 Hz
Temperature range	Single range

Model	Flir K95
Contrast optimization	Flexible Scene Enhancement (FSX®)
Image modes	Basic, Search, Detection, High Heat, White Hot
Zoom	2x digital zoom
Measurement	
Object temperature range	Single range solution operating: -20°C to 650°C (-4°F to 1202°F)
Video and images	
Storage media	Internal flash memory
Image storage formats	Standard JPEG
Media gallery	Camera and Flir Responder app

Specifications subject to change. For the most up-to-date specifications, visit flir.com.

For technical or sales support, please visit:
www.support.flir.com/kxx-series

www.flir.com

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne Flir, LLC products, please contact exportquestions@flir.com. ©2025 Teledyne Flir, LLC. All rights reserved.

Revised 07/08/2026


K95_FLIR_Datasheet-en-US

Specifications, cont.

Model	Flir K95
Image storage capacity	200 files in total (N.B. The total number of files varies dependent on the number of saved video clips)
Non-radiometric IR video recording	MPEG4 to internal flash memory
Non-radiometrics IR video streaming	Uncompressed colorized video using USB and MPEG-4 Stream over Wi-Fi to Flir Responder app
Data communication interfaces	
Interfaces	Update via OTA (Wi-Fi using the Flir Responder app) Legacy support for updates from PC and data transfer to and from PC
USB	USB-C
Wi-Fi	IEEE 802.11 b/g/n (2.4 GHz)
Bluetooth®	Bluetooth v. 5.0 EDR + BLE *PAN
Power system	
Battery type	Li-Ion
Battery voltage	3.6 V
Battery capacity	6.2 Ah, at 20°C to 25°C (68°F to 77°F)
Battery operating time	Approx. 4 hours @ 25°C (77°F) ambient temperature and typical use
Charging system	Desktop 2-bay charger Optional in-truck charger
Charging time	<3 h to capacity enough for 3 h operation
Charging temperature	0°C to 45°C (32°F to 113°F)
Power management	For documents like MSDS and UN38.3 test reports/summaries, see: https://support.flir.com/resources/msds
Power options	Automatic shutdown and sleep mode
Environmental data	
Operating temperature range	-20°C to 60°C (-4°F to 140°F) 150°C (302°F): 15 min 260°C (500°F): 5 min
Storage temperature range	-40°C to 85°C (-40°F to 185°F)
Humidity (operating and storage)	IEC 60068-2-30/24 h 95
Relative humidity	95% relative humidity 25°C to 40°C (77°F to 104°F) non-condensing

Model	Flir K95
EMC	EN 301 489-1 RED EN 301 489-17 EN 55032 Class B (Emission) EN 55035 (Immunity) EN 61000-6-2 Immunity according to Industrial EN 61000-6-3 380-480MHz EN 61000-6-3 800-960MHz EN 60945 Maritime equipment FCC 47 CFR part 15 B, class B (Emission) ICES-003
Magnetic fields	EN 61 000-4-8, Test level 5 for continuous field (severe industrial environment)
Radio spectrum	ETSI EN 300 328 ETSI EN 301 893 FCC 47 CFR part 15 RSS-247
Encapsulation	IP67 (IEC 60529)
Shock	25 g (IEC 60068-2-27)
Vibration	2 g (IEC 60068-2-6)
Drop	2 m (6.6 ft) on concrete floor (IEC 60068-2-31)
Safety (power supply)	CE/EN/UL/CSA/PSE 60950-1 IEC 62368
Physical data	
What's included?	Infrared camera Battery (2 ea.) Battery charger Carabiner strap Power supply Printed documentation Retractable lanyard, 16 N (58 oz) USB cable
Ordering information	
P/N	18706-0601

Scan below to learn more about Flir Kxx-Series



Specifications subject to change. For the most up-to-date specifications, visit flir.com.

For technical or sales support, please visit:
www.support.flir.com/kxx-series

www.flir.com

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne Flir, LLC products, please contact exportquestions@flir.com. ©2025 Teledyne Flir, LLC. All rights reserved.

Revised 09/10/2025

Kxx_FLIR_Datasheet-en-US