

# BLADE™ 95

## Combination Smoothbore Nozzle



### Overview

The HEN® BLADE™ combination smoothbore nozzle redefines fire attack by combining the reach and penetration of a traditional smoothbore with the versatility of an in-line BLADE™ pattern. With a simple quarter turn, firefighters can transition from a tight solid stream to a wide, high-impact BLADE™ stream, delivering large water droplets for maximum efficiency, improved cooling, and enhanced control.

### Specifications

|                      | IMPERIAL | METRIC  |
|----------------------|----------|---------|
| Target Flow          | 95 gpm   | 350 lpm |
| Target Pressure      | 100 psi  | 7 bar   |
| BLADE™ Pattern Angle | 22°      | 22°     |
| Weight               | 1.2 lb   | 0.54 kg |
| Length               | 5.7 in.  | 145 mm  |
| Width                | 2.7 in.  | 69 mm   |

### Coverage

| WIDTH | REACH |
|-------|-------|
| 10'   | 25'   |
| 8'    | 20'   |
| 6'    | 15'   |
| 4'    | 10'   |
| 2'    | 5'    |

### Features

- Quarter-turn from solid linear BLADE™ pattern to solid tight pattern
- Hard-coat anodized aluminum construction
- Available with 1.5" NH and 1.5" NPSH threads
- Full-time swivel
- NFPA 1960/1964 compliant
- 5-Year Warranty

### Flow Rates

| PRESSURE PSI (BAR) | FLOW RATE GPM (LPM) |
|--------------------|---------------------|
| 50 (3.4)           | 67 (253)            |
| 75 (5.2)           | 82 (310)            |
| 100 (6.9)          | 95 (358)            |
| 125 (8.6)          | 106 (400)           |
| 150 (10.3)         | 116 (438)           |



**NFPA  
COMPLIANT**