

HYDRO 138

Shutoff



Overview

HYDRO shutoff with 1.375 inch waterway. High durability shutoff with full-ball valve, designed for superior flow performance while minimizing resistance and enhancing firefighter control. The HYDRO shutoff provides superior flow with less waterway turbulence.

Features

- Gate-ball design maintains stream quality when baled-down
- Lightweight
- Hard-coat anodized aluminum body and all-metal ball
- Inlet Threads: 1.5" NH, 1.5" NPSH, 2.5" NH, and 2.5" NPSH
- Outlet Threads: 1.5" NH, and 1.5" NPSH
- Full-time swivel
- NFPA 1964 compliant
- 5 Year Warranty
- Pistol grip available

Specifications

	IMPERIAL	METRIC
Waterway Size	1.375 in.	35 mm
Rated Pressure	200 psi	14 bar
Weight (1.5" / 2.5" thread)	1.9 / 2.3 lbs	0.88 / 1.04 kg
Length (1.5" / 2.5" thread)	5.4 / 5.4 in.	137 / 137 mm
Width (1.5" / 2.5" thread)	4.2 / 4.2 in.	107 / 107 mm
Height (1.5" / 2.5" thread)	4.9 / 5.4 in.	124 / 137 mm



**NFPA
COMPLIANT**