

SENS T® GOLD

VERSATILE MULTIPLE GAS DETECTION INSTRUMENT

SENSIT® GOLD is designed to provide personal protection from potentially hazardous conditions and help find the source of combustible gases fast! Whether you need an investigation tool or a confined space monitor, you can depend on the SENSIT® GOLD to provide the safety and accuracy you need.

Displays Up To 4 Gases

- LEL (PPM Optional)
- Oxygen
- Carbon Monoxide
- Hydrogen Sulfide
- Hydrogen Cyanide (Optional)

GOLD Standard Features

- Internal Pump
- Water/Dust Filter
- Push Button Operation
- Field Calibration
- Date/Time Display
- Calibration Alert
- Operation Memory
- Calibration Memory
- Infrared Download
- Audible/Visual Alarms
- Bright LCD Display
- Programmable Auto Shut Off



INDUSTRY USERS

Utilities

Maintenance

Fire Departments

Safety Inspectors

Home Inspectors

Water/Sewer Departments

Heating Contractors

Utility Contractors

Industrial Plants

Propane Marketers



APPLICATIONS

Gas Leak Survey/Investigations
Confined Space Monitoring
Gas Emergency Investigations
Vessel Testing



PARTIAL LIST OF GASES SENSED*

Butane

Carbon Monoxide

Gasoline

Hydrogen Sulfide

Methane

Natural Gas

Oxygen

Propane

*Contact Sensit Technologies for more info.





STANDARD KIT

KIT OPTIONS

Hard Carrying Case 3 "C" Batteries Extra Sensor Cap Wrist Strap Instruction Manual Recharger Kit Printer PC Interface Hot Air Probe Confined Space Probe Calibration Kit

OPTIONAL FEATURES

Data Logging Adjustable Alarms Infrared Printer Compatiblity

ADDITIONAL FEATURES

Calibration Due Reminder

SENSOR SPECIFICATIONS

TYPE	RESOLUTION	RANGE	ACCURACY
LEAK (CSA)	N/A	50-50,000 ppm	N/A
LEAK (UL)	N/A	10-50,000 ppm	N/A
PPM* (CSA)	1 or 10 ppm	0-2,000 ppm	±10%
PPM* (UL)	1 or 10 ppm	0-2,000 ppm	±10%
LEL	0.1% up to 2.0%	0-100% LEL	±10%
O2	0.1%	0-25%	±0.2% or 2%**
CO	1 ppm	0-2000 ppm	±5 ppm or 5%**
H2S	1 ppm	0-100 ppm	±2 ppm or 5%**
HCN	1 ppm	0-30 ppm	±1 ppm or 2.5%**
*PPM Optional			**Whichever is greater

PRODUCT SPECIFICATIONS

Size: 11.5" x 3" x 2.32" (29.2 x 7.6 x 6.9 cm)

Weight: 1.2 lb. (0.5 kg)

Operational Temp: -0 to 120 F (-17.78 to 48.9° C)

Battery Life: Alkaline: Approximately 12 hrs. Continuous



Approved C22.2 No. 152 and C22.2 No. 157 For Exia Class I, Div. 1, Groups C & D, T3 hazardous locations when used with Duracell MN1400BK batteries or equivalent alkaline cells.



SENSIT® GOLD instruments are approved UL913, For Class 1, Division 1, Groups C and D hazardous locations when used with Duracell MN1400BK batteries or equivalent alkaline batteries.

SENSIT GOLD ACCESSORIES (LEL) (PPM* + LEL)

SMART-CAL Auto Calibration Station Only Part #914-00000-01

SMART-Cal Standard Gas Kit 221 Liter (Not for use with H2S, Propane or 100% CH4) Part # 881-00045

Smart-Cal 58 liter H2s Cal Kit only Part # 881-00047

Manual Calibration Kits are available. Please contact factory for price and part number.

21 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-080021

103 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-140001

221 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-180028

21 liter 1.1% Propane/Air Part # 315-080022

58 liter Hydrogen Sulfide (25ppm H2S/Air) Part # 315-120001

Sensor Cap (Replacement) w/"O" Rings Part # 870-00018

Extension Adapter Part # 870-00012

Hot Air Probe Part # 883-00023

Confined Space Probe Part # 883-00015

PC Interface with Software Part # 870-0008

Printer (Infrared)
Part # 870-0004

The following accessories to be used with the SENSIT GOLD (LEL + % V/V) (PPM* + LEL + % V/V)

21 liter 100% Methane Part # 315-080007

Demand Regulator – Use with Line Gas Part # 880-00007

2pc Probe Assembly Part # 883-00036

30" Brass Probe (5/16 OD) Part # 883-00018

32" Fiberglass Probe Part # 883-00019

Purge Probe (Brass) Part # 883-00030

Plunger Bar 42" Part # 870-00010

Hydrocarbon Filter Kit (6 pack) Part # 873-00015

Inline "Mini" Hydrocarbon Filter Kit (10 pack – BH probe with filter required) Part # 873-00012

*PPM Optional

For more information, visit www.gasleaksensors.com

Distributed by:



MADE IN USA

851 Transport Drive Valparaiso, IN 46383-8432

Phone: 888 4SENSIT 888 473 6748 219 465 2700

Fax: 219 465 2701

www.gasleaksensors.com

SENSIT Technologies is in compliance with ISO 9001:2008









