



Innovative Chemical Solutions for the Public Safety Industry

Shield Solutions, LLC

W1737 Washington Rd, Oconomowoc, WI 53066 USA | 920-474-7502 ~ 877-474-7501 ~ www.shieldsolutionsllc.com

Foaming Bug Wash Directions

Pump-up Foam Sprayer Application Method

1. Attach the white foam tip to the spray nozzle.
2. Fill the container to the 1.5lt mark with Shield Solutions™ Foaming Bug Wash. Pump 15-20 times to achieve desired pressure.
3. Spray a generous amount of foam onto the desired area to be cleaned. Let the foam dwell as long as it will cling.
4. Gently scrub the foamed area with a Shield Solutions Telescoping Brush. Rinse well and dry with a Micro Fiber Towel.

**** For best results, do not rinse the foamed area but rather follow with a complete wash with Shield Solutions™ Vehicle Wash. Rinse thoroughly, repeat if necessary.**

Cautions and Warnings

• Do not ingest • Avoid eye contact • Wear safety goggles or safety glasses with side shields for splash protection • Overexposure may cause slight irritation or dryness to skin • Vapor mist may cause irritation • Product may cause nausea if ingested • For sensitive skin, use rubber gloves • Use in well ventilated area • Do not allow product to dry on surface • Thoroughly rinse vehicle after washing • Try product on small inconspicuous area first • Keep product out of direct sunlight • Protect from freezing • Store in a cool dry area, do not store near flames or other heat sources • Keep containers tightly closed • Make sure all containers are properly labeled • Wash hands thoroughly after handling • Read and understand the MSDS before using any chemical product
Rev. 5/5/2011