



Innovative Chemical Solutions for the Public Safety Industry

Shield Solutions, LLC

P: 920.474.7502, 877.474.7501 | F: 920.474.7497 | www.shieldsolutionsllc.com

Vehicle Wash Directions

Hose End Foamer Application Method

- 1.) Attach spray nozzle to hose. Pour up to 96 ounces (2.8l) of Shield Solutions™ Vehicle Wash into the Hose-end Foamer reservoir.
- 2.) Excessive dirt and road grime should be rinsed from vehicle prior to applying the vehicle wash.
- 3.) Apply product to vehicle surface from a distance of approximately 3' to 6' (1m to 3m) from the vehicle. Start at the highest point and continue down the vehicle with a quick "zigzag" pattern across the side of the vehicle. It is not necessary to coat the entire surface of the vehicle.
- 4.) Lightly scrub the foamed area with a Shield Solutions™ Telescoping Brush (soft bristle). Caution: use of an aggressive, dirty or stiff bristle brush may scratch vehicle surface.
- 5.) Detach the Hose-end Foam Sprayer and thoroughly rinse from top to bottom.
- 6.) Squeegee or dry the windows and flat horizontal surfaces or any stainless steel, aluminum or chromed areas with a Micro-Fiber Towel.

Bucket Wash Method

- 1.) Add 2-3 ounces (59.2ml -88.7ml) of product per gallon (3.78l) of water to wash bucket.
- 2.) Excessive dirt and road grime should be rinsed from vehicle prior to applying the vehicle wash.
- 3.) Dip Shield Solutions™ Telescoping Brush (soft bristle) into bucket. Apply product from the highest point of the vehicle to the lowest point. Move around the vehicle with an overlapping pattern (scrub lightly). Caution: use of an aggressive, dirty or stiff bristle brush may scratch vehicle surface
- 4.) Thoroughly rinse vehicle from top to bottom.
- 5.) Squeegee or dry the windows and flat horizontal surfaces or any stainless steel, aluminum or chromed areas with a Micro-Fiber Towel.

Pressure Washer Method

- 1.) Consult Pressure Washer manufacturer's manual regarding proper product dispensing.
- 2.) Excessive dirt and road grime should be rinsed from vehicle prior to applying the vehicle wash.
- 3.) Apply product to vehicle surface from a distance of approximately 3' to 6' (1m to 3m) from the vehicle. Start at the highest point and continue down the vehicle.
- 4.) Lightly scrub the foamed area with a Shield Solutions™ Telescoping Brush (soft bristle). Caution: use of an aggressive, dirty or stiff bristle brush may scratch vehicle surface.
- 5.) Thoroughly rinse vehicle from top to bottom.
- 6.) Squeegee or dry the windows and flat horizontal surfaces or any stainless steel, aluminum or chromed areas with a Micro-Fiber Towel.

Do not wash in direct sunlight, or when vehicle surface is hot.

Cautions and Warnings

• Do not ingest • Avoid eye contact • Wear safety goggles or safety glasses with side shields for splash protection • Overexposure may cause slight irritation or dryness to skin • Vapor mist may cause irritation • Product may cause nausea if ingested • For sensitive skin, use rubber gloves • Use in well ventilated area • Do not allow product to dry on surface • Thoroughly rinse vehicle after washing • Try product on small inconspicuous area first • Keep product out of direct sunlight • Protect from freezing • Store in a cool dry area, do not store near flames or other heat sources • Keep containers tightly closed • Make sure all containers are properly labeled • Wash hands thoroughly after handling • Read and understand the MSDS before using any chemical product