

The multi-function, C1D1 safety-rated Survivor Pivot features a dual beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.



- Survivor Pivot securely locks into the charger
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



<p><b>Spot:</b> High: 300 lumens; 369m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 184m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)</p> <p><b>Flood:</b> High: 300 lumens; 35m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 17m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)</p> <p><b>Combo:</b> High: 325 lumens; 276m beam distance; runs 3.75 hours (Li-Ion); runs 4.5 hours (alk) Low: 80 lumens; 141m beam distance; runs 13 hours (Li-Ion); runs 12 hours (alk)</p> <p>Uses rechargeable lithium-ion battery pack (charges in 5 hours) or three (3) AA alkaline batteries (requires optional battery carrier)</p> <p>Non-Magnet: Li-Ion: 16.2 oz (459 g) Alkaline: 16.7 oz (473 g) Magnet: Li-Ion: 17.6 oz (499 g) Alkaline: 18.1 oz (513 g)</p> <p>Height: 7.93 in (20.14 cm); Width: 2.86 in (7.26 cm) Thickness: 3.29 in (8.36 cm); Thickness (w/ magnet): 3.64 in (9.25 cm)</p>	<p>Unbreakable polycarbonate lens with scratch-resistant coating</p> <p>Class I &amp; II, Division 1, Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4 (<b>Pending approval</b>) Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018) Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position</p> <p>IP67-rated; dust-tight and waterproof to 1m for 30 minutes</p> <p>Limited Lifetime Warranty Visit <a href="http://streamlight.com">streamlight.com</a> for full warranty information</p>																				
	<table border="1"> <thead> <tr> <th>Description</th> <th>Orange w/o Magnet</th> <th>Yellow w/o Magnet</th> <th>Orange w/ Magnet</th> <th>Yellow w/ Magnet</th> </tr> </thead> <tbody> <tr> <td>Survivor Pivot - 120V/100V AC/12V DC</td> <td>91802</td> <td>91812</td> <td>91830</td> <td>91831</td> </tr> <tr> <td>Survivor Pivot - 230V AC/12V DC</td> <td>91803</td> <td>91813</td> <td>91832</td> <td>91833</td> </tr> <tr> <td>Survivor Pivot - Alkaline</td> <td>91800</td> <td>91810</td> <td>91825</td> <td>91826</td> </tr> </tbody> </table>	Description	Orange w/o Magnet	Yellow w/o Magnet	Orange w/ Magnet	Yellow w/ Magnet	Survivor Pivot - 120V/100V AC/12V DC	91802	91812	91830	91831	Survivor Pivot - 230V AC/12V DC	91803	91813	91832	91833	Survivor Pivot - Alkaline	91800	91810	91825	91826
Description	Orange w/o Magnet	Yellow w/o Magnet	Orange w/ Magnet	Yellow w/ Magnet																	
Survivor Pivot - 120V/100V AC/12V DC	91802	91812	91830	91831																	
Survivor Pivot - 230V AC/12V DC	91803	91813	91832	91833																	
Survivor Pivot - Alkaline	91800	91810	91825	91826																	