



BT 1.5



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	16.00 IN	406.4 MM
WIDTH	10.75 IN	273.0 MM
HEIGHT	15.25 IN	387.3 MM
WEIGHT	28.5 LBS	12.93 KG
MOTOR	HONDA GXH50 4 STROKE	
DISPLACEMENT	49.4 CC	
FUEL TANK CAPACITY	0.20 US GALLON	0.76 LITER
APPROXIMATE RUN TIME	0.82 HOURS	
ENGINE OIL	SEE HONDA'S OWNER'S MANUAL	
HYDRAULIC PUMP	2 STAGE RADIAL PISTON OVER PISTON	
TOOL OPERATION	SINGLE TOOL OPERATION	
RESERVOIR CAPACITY	0.50 US GALLON	1.89 LITER
MFG. TO NFPA 1936-2015	YES	
ALTERNATING MODE	STANDARD	METRIC
1ST STAGE SETTING	3,500 PSI	241 BAR
1ST STAGE FLOW	196 CU IN/MIN	3,211.9 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	77 CU IN/MIN	1,261.8 CC/MIN

TNT RESCUE SYSTEMS, INC.
 2490 West Oak Street
 Ashippun, WI 53003
www.TNTRESCUE.com

