



BT 6.5

BT 6.5

TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	21.20 IN	538.5 MM
WIDTH	15.50 IN	393.7 MM
HEIGHT	15.00 IN	381.0 MM
WEIGHT	76.0 LBS	34.5 KG
MOTOR	HONDA GX200 4 STROKE	
DISPLACEMENT	196 CC	
FUEL TANK CAPACITY	0.95 US GALLON	3.6 LITER
APPROXIMATE RUN TIME	2.0 HOURS	
ENGINE OIL	SEE HONDA'S OWNER'S MANUAL	
HYDRAULIC PUMP	2 STAGE RADIAL PISTON OVER PISTON	
TOOL OPERATION	2 TOOL SIMULTANEOUS OPERATION	
RESERVOIR CAPACITY	0.90 US GALLON	3.4 LITER
MFG. TO NFPA 1936-2015	YES	
ALTERNATING MODE	STANDARD	METRIC
1ST STAGE SETTING	3,200 PSI	241 BAR
1ST STAGE FLOW	245 CU IN/MIN	4,014.8 CC/MIN
2ND STAGE SETTING	10,500 PSI	724 BAR
2ND STAGE FLOW	85 CU IN/MIN	1,392.9 CC/MIN

TNT RESCUE SYSTEMS, INC.
 2490 West Oak Street
 Ashippun, WI 53003
www.TNTRESCUE.com

