



TWIN ATT



TECHNICAL SPECS	STANDARD	METRIC
MAX. WORKING PRESSURE	10,500 PSI	724 BAR
LENGTH	22.00 IN	558.8 MM
WIDTH	10.30 IN	261.6 MM
HEIGHT	12.39 IN	314.7 MM
WEIGHT	77.0 LBS	34.9 KG
MOTOR	HYDRAULIC PISTON MOTOR	
INPUT MOTOR FLOW	10 GPM	37.9 LPM
MAX. INPUT PRESSURE	3,000 PSI	206.7 BAR
HYDRAULIC PUMP	SINGLE STAGE PISTON OVER PISTON	
TOOL OPERATION	2 TOOL SIMO OR 1 TOOL ACCELERATOR	
RESERVOIR CAPACITY	0.90 US GALLON	3.41 LITER
SINGLE STAGE SETTING	10,500 PSI	724 BAR
SINGLE STAGE FLOW	245 CU IN/MIN EACH SIDE	4,014.8 CU/MIN
MFG. TO NFPA 1936-2015	YES	

ALTERNATING ACCELERATION MODE (PER TOOL)	STANDARD	METRIC
SINGLE STAGE SETTING	490 CU IN/MIN	8,029.6 CC/MIN
SINGLE STAGE FLOW	10,500 PSI	724 BAR

TNT RESCUE SYSTEMS, INC.
2490 West Oak Street
Ashippun, WI 53003
www.TNTRESCUE.com

