



STORM SURGE

ES100-28-18V-20V

LENGTH	34.80 IN	883.99 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	48.20 LBS	21.86 KG
BATTERY WEIGHT:		
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG
MAX. SPREAD DISTANCE	27.50 IN	698.50 MM
MAX. SPREAD FORCE RANGE	56,128- 228,126 LBF	249-1,014 KN
MAX. PULL DISTANCE	18.25 IN	463.55 MM
MAX. PULL FORCE	11,168 LBF	49.67 KN
POWER SOURCE OPTION	MILWAUKEE M18	
CERTIFIED TO NFPA 1936-2020	YES	
IP RATING	54	



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.

