



ETLS-40-18V-20V

CLOSED LENGTH	21.50 IN	546.10 MM	
EXTENDED LENGTH	42.25 IN	1073.15 MM	
HEIGHT	10.75 IN	273.00 MM	
WIDTH	8.10 IN	205.70 MM	
WEIGHT			
EXCL. BATTERY	38.75 LBS	17.57 KG	
BATTERY WEIGHT:			
MILWAUKEE M18-9AH:	2.4 LBS	1.08 KG	
DEWALT 20/60V-9AH:	3.4 LBS	1.54 KG	
MAKITA 18V LXT-6AH	1.5 LBS	0.68 KG	
1 ST STAGE STROKE	12.95 IN	329.00 MM	
1 ST STAGE MAX. PUSH FORCE	38.067 LBF	169.33 KN	
2 ND STAGE STROKE	8.70 IN	221.00 MM	
$2^{\mbox{\tiny ND}}$ stage Max. Push force	13.088 LBF	58.21 KN	
POWER SOURCE OPTION	MILWAUKEE M18		
CERTIFIED TO NFPA 1936-2020	YES		



TNT hydraulic rescue tools can be used by emergency rescue personnel during vehicle accidents, as well as in other rescue scenarios such as confined spaces, structural collapses, and forcible entry situations. These tools include cutters, spreaders, combination tools, and rams, and are available in gas, battery, and air-driven versions. More information about use and capabilities can be obtained from your local distributor.





